BELGIAN BRICK



Installation Specifications

At **www.CORONADO.com** product specifications can be downloaded in CSI format.

Choices Specific to Belgian Brick

Standard Colors:	Bear Creek, Brookside, Gold Quartzite, Light Grey or Any Custom Color
Grout Joint Width:	1/2" Grout Joint
Grouting Options:	Deep Raked, Full Brushed or Full Tooled
Grout Joint Color:	Natural Grey, Natural Off-White or Complementary Color
Accessories:	Corners, Complementary Tiles, Wall Caps and more. (See Accessories section of binder)

Special Installation Notes

Pattern:	Do not install bricks vertically. Blend the bricks on the wall from several different boxes to ensure proper color and size variation. See catalog photos for recommended installation pattern.
Chalk Lines:	Should be used by installer to ensure a straight and level pattern.
Sealing:	Not required. However, if installed on an exterior exposed to excessive water from runoff or improper drainage, we suggest the product be sealed in that particular area to protect it from staining or spalling during freeze-thaw cycles.
Freeze-Thaw:	When installing stone in a freeze-thaw environment, extra care should be taken to ensure a full coverage of mortar on the back of each stone, which will prevent water pooling behind the stone after it's been installed.
Installation Info:	Download Coronado's latest installation instructions at www.coronado.com for information on mortar and installation recommendations.
Profile Properties	

Size: Brick size is 2½" (±¼16") in height and 7¾" (±¼8") in length (nominal). Thickness: ¾" average Weight: 4 to 6 lbs. per square foot. Packaging: Available in a brick box (11 sq ft Flats & 10.5 lft Corners). When purchasing Belgian Brick, coverage is based on installation with a ½" joint.

1/2" Smooth Brushed Grout Joint (Matching Grout)



1/2" Smooth Brushed Grout Joint



Belgian Brick

COLOR: BEAR CREEK

Belgian Brick

COLOR: BROOKSIDE