QUICK STACK®



Installation Specifications

At www.CORONADO.com product specifications can be downloaded in CSI format.

Choices Specific to Quick Stack®

Standard Colors: Antique Cream, Aspen, Cape Cod Grey, Cathedral Grey, Carmel Mountain, Coastal Brown, Four Rivers,

Grey Quartzite, Rustic Slate, Sahara Blend or Any Custom Color

Grout Joint Width: Drystacked **Grouting Options:** Drystacked

Grout Joint Color: Color should be added to mortar to complement stone color.

Accessories: Corners, Complementary Tiles, Wall Caps, Post Caps and more. (See Accessories section of binder)

Special Installation Notes

Pattern: Quick Stack® consists of stones that are 2" and 4" in height, which allows the installer to periodically break up long

horizontal joints. Do not install stones vertically. Blend the stone on the wall from several different boxes to ensure

proper color and size variation. See catalog photos for recommended installation pattern.

Chalk Lines: Should be used by installer to ensure a straight and level pattern.

Sealing: Not required. However, if installed on an exterior exposed to excessive water from runoff or improper drainage, we

suggest the product be sealed in that particular area to protect it from staining or spalling during freeze-thaw cycles.

Freeze-Thaw: When installing stone in a freeze-thaw environment, extra care should be taken to ensure a full coverage of mortar

on the back of each stone, which will prevent water pooling behind the stone after it's been installed.

Drystacked: A polymer modified mortar should be used for all drystacked applications.

Installation Info: Download Coronado's latest installation instructions at www.coronado.com for information on mortar and

installation recommendations.

Profile Properties

Size: Quick Stack® is a combination of individual stones and panelized stones, which makes it easier to install and

harder to detect the panels. Stone sizes are 2" or 4" in height and up to 20" in length. Stones sizes within the panels

range from 1/2" to 4" in height. (All sizes are nominal).

Thickness: 1" to 2"

Weight: 7 to 10 lbs. per square foot.

Packaging: Available in big boxes (100 sq ft Flats & 100 lft Corners) or Dura-Paks (12.5 sq ft Flats & 12.5 lft Corners).

When purchasing Quick Stack®, coverage is based on installation with tightly-fitted joints.

Drystacked

Quick Stack



COLOR: CARMEL MOUNTAIN

Drystacked



QUICK STACK

COLOR: CAPE COD GREY